

■ 2178 Baler Moisture Meter PLUS



Multi Sensor On The Go Moisture Reading

The 2178 with multi-sensor technology takes readings on the left and right side, as well as through the bale, for greater accuracy.

The 2178 mounts in the cab of the tractor and provides a direct readout for % moisture while baling hay. Having multiple moisture content readings during each step of the hay making process is critical to finishing with a high quality product.

Features

- Bale type: small square and round
- Multi-sensor technology takes readings from the left, right and middle of the bale for greater overall accuracy
- Average of readings updated and displayed every 3 seconds
- Large, illuminated LCD display and keypad for easy viewing during day or night
- ± Moisture offset adjustments
- Adjustable high/low limit of moisture reading
- Firmware/calibration curves upgradable via standard USB

Includes

- Display module
- 3m power cable
- Two sensor pads
- Two 10x sensor cables
- Twelve sensor cable ties
- Mounting Hardware
- USB Cable
- Installation instructions

Operating Range (Moisture): 8% to 40% depending on baler type used
Accurate throughout the normal range of stored hay
Display Resolution: 0.1% moisture

Order Code	
2178	In Chamber Baler Moisture PLUS Sensor Kit



Spare Parts

Order Code	
2178S	In Chamber Moisture PLUS Sensor Replacement (Single)



Order Code		SUITS 2177 & 2178
2177C	3.5m Extension Cable (Packard to Packard Extension)	
2177SC	8.5m Extension Cable (Packard to Ring Terminals for Sensor)	
2178C	10.5m Extension Cable (Packard to Ring Terminals for Sensor)	

2177 - Single in chamber Parts

Order Code	
2177S	In Chamber Moisture Sensor Replacement

